



- 材质: DIN C45
- 螺纹精度: ISO 6H
- 端面偏摆: 0.005

| 型号 | 螺纹和间距 | 尺寸 | | | | | | |
|--------|-------------|-----|------|-----|----|------|----|-----|
| | | D | d | B | h | H | g | t |
| ANT 00 | M 10 × 0.75 | 18 | 13.5 | 14 | 4 | 5.2 | 3 | 2 |
| ANT 01 | M 12 × 1.0 | 22 | 17 | 18 | 4 | 5.4 | 3 | 2 |
| ANT 02 | M 15 × 1.0 | 25 | 21 | 21 | 5 | 6.5 | 4 | 2 |
| ANT 03 | M 17 × 1.0 | 28 | 24 | 24 | 5 | 6.4 | 4 | 2 |
| ANT 04 | M 20 × 1.0 | 32 | 26 | 28 | 6 | 7.7 | 4 | 2 |
| ANT 05 | M 25 × 1.5 | 38 | 32 | 34 | 7 | 9.1 | 5 | 2 |
| ANT 06 | M 30 × 1.5 | 45 | 38 | 41 | 7 | 9.1 | 5 | 2 |
| ANT 07 | M 35 × 1.5 | 52 | 44 | 48 | 8 | 10.2 | 5 | 2 |
| ANT 08 | M 40 × 1.5 | 58 | 50 | 53 | 9 | 11.2 | 6 | 2.5 |
| ANT 09 | M 45 × 1.5 | 65 | 56 | 60 | 10 | 12.5 | 6 | 2.5 |
| ANT 10 | M 50 × 1.5 | 70 | 61 | 65 | 11 | 13.5 | 6 | 2.5 |
| ANT 11 | M 55 × 2.0 | 75 | 67 | 69 | 11 | 13.5 | 7 | 3 |
| ANT 12 | M 60 × 2.0 | 80 | 73 | 74 | 11 | 13.5 | 7 | 3 |
| ANT 13 | M 65 × 2.0 | 85 | 79 | 79 | 12 | 15 | 7 | 3 |
| ANT 14 | M 70 × 2.0 | 92 | 85 | 85 | 12 | 15 | 8 | 3.5 |
| ANT 15 | M 75 × 2.0 | 98 | 90 | 91 | 13 | 15.8 | 8 | 3.5 |
| ANT 16 | M 80 × 2.0 | 105 | 95 | 98 | 15 | 18.6 | 8 | 3.5 |
| ANT 17 | M 85 × 2.0 | 110 | 102 | 103 | 16 | 19.2 | 8 | 3.5 |
| ANT 18 | M 90 × 2.0 | 120 | 108 | 112 | 16 | 20.3 | 10 | 4 |
| ANT 19 | M 95 × 2.0 | 125 | 113 | 117 | 17 | 21.3 | 10 | 4 |
| ANT 20 | M 100 × 2.0 | 130 | 120 | 122 | 18 | 22.3 | 10 | 4 |

备注 1. NUT 承接 M2 ~ M1000 各种材质、非标准螺距以及特殊外型螺母的订制
 2. 如您订购左旋螺纹之螺母时, 请加注 -L 例: NFM30 × 1.5 P-L
 3. 以上资料仅供参考, 本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft