



- 材质: DIN C45
- 硬度: HRC 28-32°
- 螺纹精度: ISO 6H
- 端面偏摆: 0.005

型号	螺纹和间距	尺寸						
		D	d	d1	B	h	g	t
HN 42	Tr 210 × 4.0	270	238	212	250	30	20	10
HN 44	Tr 220 × 4.0	280	250	222	260	32	20	10
HN 48	Tr 240 × 4.0	300	270	242	280	34	20	10
HN 52	Tr 260 × 4.0	330	300	262	306	36	24	12
HN 58	Tr 290 × 4.0	370	330	292	346	40	24	12
HN 62	Tr 310 × 5.0	390	350	312.5	366	42	24	12
HN 66	Tr 330 × 5.0	420	380	332.5	390	52	28	15
HN 70	Tr 350 × 5.0	450	410	352.5	420	55	28	15
HN 74	Tr 370 × 5.0	470	430	372.5	440	58	28	15
HN 80	Tr 400 × 5.0	520	470	402.5	484	62	32	18
HN 84	Tr 420 × 5.0	540	490	422.5	504	70	32	18
HN 88	Tr 440 × 5.0	560	510	442.5	520	70	36	20
HN 92	Tr 460 × 5.0	580	540	462.5	540	75	36	20
HN 96	Tr 480 × 5.0	620	560	482.5	580	75	36	20
HN 102	Tr 510 × 6.0	650	590	513	604	80	40	23
HN 106	Tr 530 × 6.0	670	610	533	624	80	40	23
HN 110	Tr 550 × 6.0	700	640	553	654	80	40	23

HNL 41	Tr 205 × 4.0	250	232	207	234	30	18	8
HNL 43	Tr 215 × 4.0	260	242	217	242	30	20	9
HNL 47	Tr 235 × 4.0	280	262	237	262	34	20	9
HNL 52	Tr 260 × 4.0	310	290	262	290	34	20	10
HNL 56	Tr 280 × 4.0	330	310	282	310	38	24	10
HNL 60	Tr 300 × 4.0	360	336	302	336	42	24	12
HNL 64	Tr 320 × 5.0	380	356	322.5	356	42	24	12
HNL 69	Tr 345 × 5.0	410	384	347.5	384	45	28	13
HNL 73	Tr 365 × 5.0	430	404	367.5	404	48	28	13
HNL 77	Tr 385 × 5.0	450	422	387.5	422	48	28	14
HNL 82	Tr 410 × 5.0	480	452	412.5	452	52	32	14
HNL 86	Tr 430 × 5.0	500	472	432.5	472	52	32	14
HNL 90	Tr 450 × 5.0	520	490	452.5	490	60	32	15
HNL 94	Tr 470 × 5.0	540	510	472.5	510	60	32	15
HNL 98	Tr 490 × 5.0	580	550	492.5	550	60	36	15
HNL 104	Tr 520 × 6.0	600	570	523	570	68	36	15
HNL 108	Tr 540 × 6.0	630	590	543	590	68	40	20

备注 1. NUT 承接 M2 ~ M1000 各种材质、非标准螺距以及特殊外型螺母的订制
 2. 如您订购左旋螺纹之螺母时, 请加注-L 例: NFM30 × 1.5 P-L
 3. 以上资料仅供参考, 本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft