



- 材质: DIN C45
- 硬度: HRC 28-32°
- 螺纹精度: ISO 4g
- 端面偏摆: 0.005

型号	尺寸							轴向载荷 (KN)
	d	D	G	d2	b	h	d1	
ND M 40 × 1.5	26	28	M40 × 1.5	31	4.3	9	27	45
ND M 50 × 1.5	36	41	M50 × 1.5	42.5	4.3	10	37.5	65
ND M 55 × 1.5	40	45	M55 × 1.5	47	4.3	10	42	77
ND M 70 × 1.5	50	56	M70 × 1.5	59.5	4.3	12	52	100
ND M 80 × 1.5	60	65	M80 × 1.5	72	4.3	12	63	130
ND M 85 × 1.5	66	72	M85 × 1.5	76	4.3	14	69	130
ND M 95 × 2.0	76	82	M95 × 2.0	84.5	6.3	14	79.5	150
ND M 110 × 2.0	76	92	M110 × 2.0	90	6.3	14	79.5	190
ND M 120 × 2.0	99	101	M120 × 2.0	106	6.3	14	103	210
ND M 130 × 2.0	99	110	M130 × 2.0	110	6.3	14	103	220
ND M 160 × 3.0	132	134	M160 × 3.0	148	6.3	18	137.3	340
ND M 190 × 3.0	162	167	M190 × 3.0	176	6.3	18	166	440

备注 1. NUT 承接 M2 ~ M1000 各种材质、非标准螺距以及特殊外型螺母的订制
 2. 如您订购左旋螺纹之螺母时, 请加注 -L 例: NFM30 × 1.5 P-L
 3. 以上资料仅供参考, 本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft