



三个等间距的锁紧销可以令螺母精准定位, 也可使需要精密公差的轴承和精密元件的调节易于操作。

- 材质: DIN C45
- 硬度: HRC 28-32°
- ┌ 螺纹精度: ISO 4H
- └ 螺纹精度: ISO 4H
- ┌ 端面偏摆: 0.002
- └ 端面偏摆: 0.005

型号	尺寸									扭紧力矩 (NM)	轴向载荷 (KN)
	D	d	d1	H	d2	L	N1	N2	m		
NFB M 20 x 1.5	38	30	21	18	29	10	4.3	4	M6	8.0	110
NFB M 25 x 1.5	42	35	26	20	32.5	11	4.3	4	M6	8.0	130
NFB M 30 x 1.5	48	40	32	20	40.5	11	4.3	5	M6	8.0	160
NFB M 35 x 1.5	53	47	38	22	45.5	11	4.3	5	M6	8.0	190
NFB M 40 x 1.5	58	52	42	22	50.5	12	4.3	5	M6	8.0	210
NFB M 45 x 1.5	68	58	48	22	58	12	4.3	6	M6	8.0	240
NFB M 50 x 1.5	70	63	52	24	61.5	13	4.3	6	M6	8.0	330
NFB M 55 x 1.5	75	70	58	24	66.5	13	4.3	6	M6	8.0	340
NFB M 60 x 1.5	84	75	62	24	74.5	13	5.3	6	M6	8.0	380
NFB M 65 x 1.5	88	80	68	24	78.5	13	5.3	6	M8	8.0	460
NFB M 70 x 1.5	95	86	72	26	85	14	5.3	8	M8	18	490
NFB M 75 x 1.5	100	91	77	26	88	13	6.4	8	M8	18	520
NFB M 80 x 2.0	110	97	83	30	95	16	6.4	8	M8	18	620
NFB M 85 x 2.0	115	102	88	32	100	17	6.4	8	M10	35	650
NFB M 90 x 2.0	120	110	93	32	108	17	6.4	8	M10	35	680
NFB M 95 x 2.0	125	114	98	32	113	17	6.4	8	M10	35	710
NFB M 100 x 2.0	130	120	103	32	118	17	6.4	8	M10	35	740
NFB M 110 x 2.0	140	132	112	32	128	17	6.4	8	M10	35	800
NFB M 120 x 2.0	155	142	122	32	140	17	6.4	8	M10	35	800
NFB M 130 x 3.0	165	156	132	32	153	17	6.4	8	M10	35	920
NFB M 140 x 3.0	180	166	142	32	165	17	6.4	10	M10	35	980
NFB M 150 x 3.0	190	180	152	32	175	17	6.4	10	M10	35	1040
NFB M 160 x 3.0	205	190	162	32	185	17	8.4	10	M10	35	1100
NFB M 170 x 3.0	215	205	172	32	195	17	8.4	10	M10	35	1160
NFB M 180 x 3.0	230	215	182	32	210	17	8.4	10	M10	35	1220
NFB M 190 x 3.0	240	225	192	32	224	17	8.4	10	M10	35	1280
NFB M 200 x 3.0	245	237	202	32	229	17	8.4	10	M10	35	1340

备注 1. NUT 承接 M2 - M1000 各种材质、非标准螺距以及特殊外型螺母的订制  
 2. 如您订购左旋螺纹之螺母时, 请加注 -L 例: NFM30 x 1.5 P-L  
 3. 以上资料仅供参考, 本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft