



三个等间距的锁紧销可以令螺母精准定位, 也可使需要精密公差的轴承和精密元件的调节易于操作。

- 材质: DIN C45
- 硬度: HRC 28-32°
- ┌ 螺纹精度: ISO 4H
- └ 端面偏摆: 0.002
- ┌ 螺纹精度: ISO 4H
- └ 端面偏摆: 0.005

型号	尺寸								扭紧力矩 (NM)	轴向载荷 (KN)
	d1	D	d	d2	h	g	t	m		
NFC M 10 × 0.75	21	28	23	11	14	4	25	M5	4.5	40
NFC M 12 × 1.0	23	30	25	13	14	4	2.5	M5	4.5	40
NFC M 15 × 1.0	26	33	28	16	16	4	2.5	M5	4.5	60
NFC M 17 × 1.0	29	37	33	18	18	5	2.5	M6	8.0	80
NFC M 20 × 1.0	32	40	35	21	18	5	2.5	M6	8.0	90
NFC M 25 × 1.5	36	44	39	26	20	5	2.5	M6	8.0	130
NFC M 30 × 1.5	41	49	44	32	20	5	2.5	M6	8.0	160
NFC M 35 × 1.5	46	54	49	38	22	5	2.5	M6	8.0	190
NFC M 40 × 1.5	56	65	59	42	22	6	3	M6	8.0	210
NFC M 45 × 1.5	61	70	64	48	22	6	3	M6	8.0	240
NFC M 50 × 1.5	65	75	68	52	25	7	3.5	M6	8.0	300
NFC M 55 × 2.0	74	85	78	58	25	7	3.5	M8	18	340
NFC M 60 × 2.0	78	90	82	62	26	8	4	M8	18	380
NFC M 65 × 2.0	83	95	87	68	28	8	4	M8	18	460
NFC M 70 × 2.0	88	100	92	72	28	8	4	M8	18	490
NFC M 75 × 2.0	93	105	97	77	28	8	4	M8	18	520
NFC M 80 × 2.0	98	110	100	83	32	8	3.5	M8	18	620
NFC M 85 × 2.0	107	120	110	88	32	10	4	M10	35	650
NFC M 90 × 2.0	112	125	115	93	32	10	4	M10	35	680
NFC M 95 × 2.0	117	130	120	98	32	10	4	M10	35	710
NFC M 100 × 2.0	122	135	125	103	32	10	4	M10	35	740
NFC M 110 × 2.0	132	145	134	112	32	10	4	M10	35	800
NFC M 120 × 2.0	142	155	144	122	32	10	4	M10	35	860
NFC M 130 × 2.0	152	165	154	132	32	12	5	M10	35	920
NFC M 140 × 2.0	162	175	164	142	32	14	6	M10	35	980
NFC M 150 × 2.0	172	185	174	152	32	14	6	M10	35	1040
NFC M 160 × 2.0	182	195	184	162	32	14	6	M10	35	1100
NFC M 170 × 2.0	192	205	194	172	32	14	6	M10	35	1160
NFC M 180 × 2.0	202	215	204	182	32	16	7	M10	35	1220
NFC M 190 × 2.0	212	225	214	192	32	16	7	M10	35	1280
NFC M 200 × 2.0	222	235	224	202	32	18	8	M10	35	1340

备注 1. NUT 承接 M2 ~ M1000 各种材质、非标准螺距以及特殊外型螺母的订制
 2. 如您订购左旋螺纹之螺母时, 请加注 -L 例: NFM30 × 1.5 P-L
 3. 以上资料仅供参考, 本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft