



该产品通过螺母本身的弹性变形,使螺纹面紧密贴合于公螺纹,实现轴向强力紧固。由于该产品外径和厚度较大,可承受更大轴向力。

- 材质: DIN C45
- 硬度: HRC 28-32°
- 螺纹精度: ISO 4H
- 螺纹精度: ISO 4H
- 端面偏摆: 0.002
- 端面偏摆: 0.005

型号	尺寸								扭紧力矩 (NM)
	G	D	d	h	c	g	t	n-M x L	
NKB4 x 28	M20 x 1.5	42	38	28	11	6	2.5	4-M4 x 16	3.5
NKB5 x 28	M25 x 1.5	47	43	28	11	7	3	4-M4 x 16	3.5
NKB6 x 28	M30 x 1.5	52	48	28	11	7	3	4-M4 x 16	3.5
NKB7 x 28	M35 x 1.5	60	53	28	11	8	3.5	4-M4 x 16	3.5
NKB8 x 28	M40 x 1.5	65	58	28	11	8	3.5	4-M4 x 16	3.5
NKB9 x 28	M45 x 1.5	70	63	28	11	8	3.5	4-M4 x 16	3.5
NKB10 x 32	M50 x 1.5	75	68	32	11	8	3.5	4-M4 x 16	3.5
NKB4	M20 x 1.5	52	42	40	11	7	3	4-M4 x 20	3.5
NKB5	M25 x 1.5	62	47	40	11	8	3.5	4-M4 x 20	3.5
NKB6	M30 x 1.5	68	57	44	11	8	3.5	4-M4 x 20	3.5
NKB7	M35 x 1.5	73	60	44	11	8	3.5	4-M4 x 20	3.5
NKB8	M40 x 1.5	75	62	44	11	8	3.5	4-M4 x 20	3.5
NKB9	M45 x 1.5	90	75	44	11	10	4	6-M4 x 20	3.5
NKB10	M50 x 1.5	95	75	46	11	10	4	6-M4 x 20	3.5
NKB11	M55 x 1.5	100	80	46	12	10	4	6-M5 x 25	6
NKB12	M60 x 1.5	100	85	46	12	10	4	6-M5 x 25	6
NKB12	M60 x 2.0	100	85	46	12	10	4	6-M5 x 25	6
NKB13	M65 x 1.5	110	90	46	12	10	4	6-M5 x 25	6
NKB13	M65 x 2.0	110	90	46	12	10	4	6-M5 x 25	6
NKB14	M70 x 1.5	115	95	46	12	10	4	6-M5 x 25	6
NKB14	M70 x 2.0	115	95	46	12	10	4	6-M5 x 25	6
NKB15	M75 x 2	120	100	46	12	10	4	6-M5 x 25	6
NKB16	M80 x 2	125	105	46	12	10	4	6-M6 x 25	8
NKB17	M85 x 2	130	110	46	12	10	4	6-M6 x 25	8
NKB18	M90 x 2	132	115	47	13	10	4	6-M6 x 25	8
NKB19	M95 x 2	140	125	47	13	12	5	6-M6 x 25	8
NKB20	M100 x 2	145	130	47	13	12	5	6-M6 x 25	8
NKB21	M105 x 2	150	135	47	13	12	5	6-M6 x 25	8
NKB22	M110 x 2	155	140	47	13	12	5	6-M6 x 25	8
NKB23	M115 x 2	160	145	48	14	12	5	6-M6 x 25	8
NKB24	M120 x 2	165	150	48	14	12	5	6-M6 x 25	8
NKB25	M125 x 2	170	155	48	14	14	6	6-M6 x 25	8
NKB26	M130 x 2	180	160	48	14	14	6	8-M6 x 25	8
NKB28	M140 x 2	190	170	50	15	14	6	8-M6 x 25	8
NKB30	M150 x 2	200	180	50	15	14	6	8-M6 x 25	8
NKB32	M160 x 3	220	190	50	15	16	7	8-M8 x 30	18
NKB34	M170 x 3	230	205	52	16	16	7	8-M8 x 30	18
NKB36	M180 x 3	240	215	52	16	16	7	8-M8 x 30	18
NKB38	M190 x 3	250	225	52	16	18	8	8-M8 x 30	18
NKB40	M200 x 3	265	235	52	16	18	8	8-M8 x 30	18

备注 1. NUT 承接 M2 - M1000 各种材质、非标准螺距以及特殊外型螺母的订制
 2. 如您订购左旋螺纹之螺母时,请加注 -L 例: NFM30 x 1.5 P-L
 3. 以上资料仅供参考, 本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft