



该产品通过螺母本身的弹性变形，使螺纹面紧密贴合于公螺纹，实现轴向强力紧固。适用于工作环境恶劣，安装空间受限，螺帽易于松脱的场合。

- 材质: DIN C45
- 硬度: HRC 28-32°
- 螺纹精度: ISO 4H
- 端面偏摆: 0.005

型号	尺寸							扭紧力矩 (NM)
	D	h	g	t	n-m	c	n-φb	
NKD M 16 × 1.5	34	14	4	2	2-M4	24	2-φ4	3.5
NKD M 17 × 1.0	37	16	4	2	2-M4	26	2-φ4	3.5
NKD M 18 × 1.5	38	16	4	2	2-M4	28	2-φ4	3.5
NKD M 20 × 1.0	40	16	4	2	2-M4	30	2-φ4	3.5
NKD M 20 × 1.5	40	16	4	2	2-M4	30	2-φ4	3.5
NKD M 25 × 1.5	45	18	5	2	2-M4	35	2-φ5	3.5
NKD M 30 × 1.5	48	18	5	2	2-M4	39	2-φ5	3.5
NKD M 35 × 1.5	53	18	5	2	2-M4	44	2-φ5	3.5
NKD M 40 × 1.5	58	20	6	2.5	2-M4	49	2-φ5	3.5
NKD M 45 × 1.5	68	20	6	2.5	2-M4	57	2-φ6	3.5
NKD M 50 × 1.5	70	20	6	2.5	2-M4	60	2-φ6	3.5
NKD M 55 × 1.5	75	22	7	3	2-M4	65	2-φ6	3.5
NKD M 55 × 2.0	75	22	7	3	2-M4	65	2-φ6	3.5
NKD M 60 × 1.5	84	22	7	3	2-M5	72	2-φ6	4.5
NKD M 60 × 2.0	84	22	7	3	2-M5	72	2-φ6	4.5
NKD M 65 × 1.5	88	22	7	3	2-M5	77	2-φ6	4.5
NKD M 65 × 2.0	88	22	7	3	2-M5	77	2-φ6	4.5
NKD M 70 × 1.5	95	24	8	3.5	2-M5	82	2-φ7	4.5
NKD M 70 × 2.0	95	24	8	3.5	2-M5	82	2-φ8	4.5
NKD M 75 × 1.5	100	24	8	3.5	6-M5	87	2-φ9	4.5
NKD M 75 × 2.0	100	24	8	3.5	6-M5	87	2-φ10	4.5
NKD M 80 × 2.0	110	24	8	3.5	6-M6	95	2-φ8	8
NKD M 85 × 2.0	115	24	8	3.5	6-M6	100	2-φ8	8
NKD M 90 × 2.0	120	26	10	4	6-M6	105	2-φ8	8
NKD M 95 × 2.0	125	26	10	4	6-M6	110	2-φ8	8
NKD M 100 × 2.0	130	26	10	4	6-M6	115	2-φ8	8
NKD M 105 × 2.0	135	28	10	4	6-M6	120	2-φ8	8
NKD M 110 × 2.0	140	28	10	4	6-M6	125	2-φ8	8
NKD M 115 × 2.0	145	28	10	4	6-M6	130	2-φ8	8
NKD M 120 × 2.0	155	30	12	5	6-M6	136	2-φ8	8
NKD M 125 × 2.0	160	30	12	5	6-M6	140	2-φ8	8
NKD M 130 × 2.0	165	30	12	5	6-M6	148	2-φ8	8
NKD M 135 × 2.0	170	32	12	5	6-M6	153	2-φ8	8
NKD M 140 × 2.0	180	32	12	5	6-M6	160	2-φ10	8
NKD M 145 × 2.0	185	32	12	5	6-M6	165	2-φ10	8
NKD M 150 × 2.0	190	32	12	5	6-M6	170	2-φ10	8
NKD M 155 × 2.0	195	34	14	6	6-M8	175	2-φ10	18
NKD M 160 × 3.0	205	34	14	6	6-M8	178	2-φ10	18
NKD M 165 × 3.0	210	34	14	6	6-M8	184	2-φ10	18
NKD M 170 × 3.0	215	34	14	6	6-M8	193	2-φ10	18
NKD M 180 × 3.0	230	36	16	7	6-M8	205	2-φ10	18
NKD M 190 × 3.0	240	36	16	7	6-M8	215	2-φ10	18
NKD M 200 × 3.0	245	38	16	7	6-M8	223	2-φ10	18

备注 1. NUT 承接 M2 ~ M1000 各种材质、非标准螺距以及特殊外型螺母的订制
 2. 如您订购左旋螺纹之螺母时，请加注 -L 例：NFM30 × 1.5 P-L
 3. 以上资料仅供参考，本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft