



锁紧螺钉的锁紧方向为径向锁紧, 适用于安装和松脱要求简易的低负载的轴承座。

- 材质: DIN C45
- 硬度: HRC 28-32°
- 螺纹精度: ISO 4H
- 端面偏摆: 0.005

型号	尺寸					
	m	D	d	h	L	F
NRA M 4 × 0.5	M2.6	11.5	8	5	2.7	10
NRA M 5 × 0.5	M2.6	13.5	9	5	2.7	11
NRA M 6 × 0.75	M3 × 0.5	14.5	10	5	2.7	12
NRA M 8 × 1.0	M3 × 0.5	17	13	6.5	4	14
NRA M 10 × 1.0	M3 × 0.5	20	16	8	5	17
NRA M 12 × 1.0	M3 × 0.5	22	17	8	5	19
NRA M 15 × 1.0	M3 × 0.5	25	21	10	6	22
NRA M 17 × 1.0	M4 × 0.7	30	25	13	9	24
NRA M 20 × 1.0	M4 × 0.7	35	26	13	8	30
NRA M 25 × 1.5	M5 × 0.8	43	33	15	10	35
NRA M 30 × 1.5	M6 × 1.0	48	39	20	14	40
NRA M 35 × 1.5	M8 × 1.25	60	46	21	14	50
NRA M 40 × 1.5	M8 × 1.25	63	51	25	18	50

备注 1. NUT 承接 M2 - M1000 各种材质、非标准螺距以及特殊外型螺母的订制
 2. 如您订购左旋螺纹之螺母时, 请加注 -L 例: NFM30 × 1.5 P-L
 3. 以上资料仅供参考, 本公司拥有修改之权利

1Nm=10.2kgf.cm=0.73lb.ft