



Model no.	Outer dimensions			LM case dimensions						
	Height M	Width W	Length L	Mounting hole position			Tap S×ℓ	Through-hole bolt S ₂	Center height J ±0.02	W ₁ ±0.02
				B	B ₁	C				
SL 6UU	18	30	48	20	5	36	M4×8	M3	9	15
SL 8UU	22	34	58	24	5	42	M4×8	M3	11	17
SL 10UU	26	40	68	28	6	46	M5×12	M4	13	20
SL 12UU	29	42	70	30.5	5.75	50	M5×12	M4	15	21
SL 13UU	30	44	75	33	5.5	50	M5×12	M4	15	22
SL 16UU	38.5	50	85	36	7	60	M5×12	M4	19	25
SL 20UU	42	54	96	40	7	70	M6×12	M5	21	27
SL 25UU	51.5	76	130	54	11	100	M8×18	M6	26	38
SL 30UU	59.5	78	140	58	10	110	M8×18	M6	30	39

LM case dimensions							Combination bushing				
K	W ₂	T	R	N	Inscribed circle diameter dr	Tolerance	Unit weight g	Model no.		Basic load rating	
								C	N	C ₀	N
15	28	6	9	7	6	0 -0.009	68	LM 6U	324	529	
18	32	6	11	7	8		105	LM 8U	431	784	
21	38	8	13	7	10		185	LM 10U	588	1100	
25	39	8	14	6.5	12		205	LM 12U	657	1200	
26	41	8	15	6.5	13		242	LM 13U	814	1570	
35	46	9	19.5	6	16		403	LM 16U	1230	2350	
36	52	11	21	7	20	520	LM 20U	1400	2750		
41	68	12	25.5	4	25	0 -0.010	1120	LM 25U	1560	3140	
49	72	15	29.5	5	30		1440	LM 30U	2490	5490	