



单位 (mm)

SWLE100 d × D	L1	L2	L3	B	D1	扭矩 Nm	轴向 推力 载荷 KN	表面压力		紧固螺栓		重量 (g)
								轴Pw N/mm <sup>2</sup>	轮 Pn N/mm <sup>2</sup>	DIN 912 12.9 NO. × type	锁紧扭矩Ms Nm	
12 × 18	15	22.5	26	30	32	58	10	160	105	4 × M4	5	80
13 × 23	15	22.5	26	30	38	63	10	140	80	4 × M4	5	125
14 × 23	15	22.5	26	30	38	68	10	130	80	4 × M4	5	120
15 × 24	16.5	28	35	41	45	127	17	185	115	3 × M6	17	257
16 × 24	16.5	28	35	41	45	136	17	175	115	3 × M6	17	250
17 × 26	18.5	30	37	43	47	180	22	190	125	4 × M6	17	280
18 × 26	18.5	30	37	43	47	200	22	180	125	4 × M6	17	270
19 × 27	18.5	30	37	43	49	210	22	170	120	4 × M6	17	290
20 × 28	18.5	30	37	43	50	220	22	160	115	4 × M6	17	300
22 × 32	25.5	38	45	51	54	250	22	115	80	4 × M6	17	385
24 × 34	25.5	38	45	51	56	270	22	105	75	4 × M6	17	405
25 × 34	25.5	38	45	51	56	280	22	100	75	4 × M6	17	390
28 × 39	25.5	38	45	51	61	465	33	135	97	6 × M6	17	475
30 × 41	25.5	38	45	51	63	510	33	127	90	6 × M6	17	480
32 × 43	25.5	38	45	51	65	540	33	120	90	6 × M6	17	520
35 × 47	32.5	45	52	58	69	790	45	105	80	8 × M6	17	630
38 × 50	32.5	45	52	58	72	860	45	100	75	8 × M6	17	670
40 × 53	32.5	45	52	58	75	900	45	95	70	8 × M6	17	735
42 × 55	32.5	45	52	58	77	950	45	90	70	8 × M6	17	780
45 × 59	45.5	61	70	78	86	1890	84	110	85	8 × M8	41	1,230
48 × 62	45.5	61	70	78	87	2010	84	105	80	8 × M8	41	1,240
50 × 65	45.5	61	70	78	92	2100	84	100	75	8 × M8	41	1,400
55 × 71	55.5	71.5	80	88	98	2600	94	85	65	9 × M8	41	1,700
60 × 77	55.5	71.5	80	88	104	2840	94	75	60	9 × M8	41	1,950
65 × 84	55.5	71.5	80	88	111	3070	94	70	55	9 × M8	41	2,200
70 × 90	65.5	86	96	106	119	5250	150	90	70	9 × M10	83	3,050
75 × 95	65.5	86	96	106	127	5600	150	80	65	9 × M10	83	3,300
80 × 100	65.5	86	96	106	132	8020	200	100	80	12 × M10	83	3,500
85 × 106	65.5	86	96	106	138	8500	200	95	75	12 × M10	83	3,800
90 × 112	65.5	86	96	106	144	9000	200	90	75	12 × M10	83	4,200
95 × 120	65.5	86	96	106	150	11000	230	100	80	14 × M10	83	4,750
100 × 125	65.5	86	96	106	155	15000	300	120	95	12 × M12	83	4,880
110 × 140	90	114	128	140	180	16000	290	80	65	12 × M12	145	8,950
120 × 155	90	114	128	140	198	17500	290	70	55	12 × M12	145	11,500
130 × 165	90	114	128	140	208	25000	384	90	70	16 × M12	145	12,100